



# Carpet Care Equipment

Designed for the Professional

## SSS Achiever 40 & 110

- Self-contained Carpet Extractor
- Dependable
- High-performance
- Easy to Maintain
- Easy to Operate



## SSS Hi-Flow Extractor

- Reduces Labor by up to 40%
- Easy to Maneuver
  - Reduces Operator Fatigue
  - Optional Upholstery Kit



## SSS Power Spotter 3

- Compact Design
- Easy to Transport
- Durable
- Expandable 12' Hose



Specifications	Achiever 40 # 54171	Achiever 110 # 54173
Solution Tank Capacity	4 gallons	11 gallons
Recovery Tank Capacity	3 gallons	9 gallons (drain valve)
Construction	Roto-molded polyethylene	Roto-molded polyethylene
Cleaning Path Width	12"	16"
Vacuum Motor	2-stage	3-stage
Vacuum Performance (water lift)	80"	137"
Pump Type/Pump PSI	Bypass/60 psi	Demand/100 psi
Injection Spray Jets	2, brass and filtered	4, brass and filtered
Scrubbing Brush, Nylon	11" x 3", chevron	14" x 4", chevron
Brush Drive	Cogged belt	Cogged belt
Length x Width x Height	39" x 12" x 34 <sup>3</sup> / <sub>8</sub> "	45" x 16 <sup>1</sup> / <sub>2</sub> " x 40"
Weight	60 pounds	100 pounds
Electrical Requirements	115 volts, 11.5 amp	115 volts, 15 amp
Power Cord	25', 16 x 3 SJT	50', 14 x 3 SJT
Warranty*	5 years on housing, 1 year on all other components	5 years on housing, 1 year on all other components

Specifications	Hi-Flow Extractor # 54240
Solution Flow Rate	4 plus gallons per minute
Solution Pressure	Average of 45 psi (determined by faucet water pressure)
Solution Temperature	Determined by the building's water source temperature
Solution Recovery Rate	94%
Pump Discharge Capacity	240 gallons per hour
On-board Spray Nozzle	Handle mounted 25' hose; adjustable head
Adjustable Pre-Spray	0.5 to 12 ounces per gallon
Detergent Injection	Detergent is automatically injected into solution @ 2 ounces/gallon
Vacuum Shoe Width	14"
Weight	33 pounds
Vacuum Response Time	0.33 seconds
Electrical Requirements	110 volts, 13 amp circuit
Warranty*	1 year parts and labor on all other components



Specifications	Power Spotter 3 # 54408
Solution Tank Capacity	2 gallons
Recovery Tank Capacity	3.5 gallons (removable)
Pump (manual)	60 psi
Vacuum Motor	One 2-stage bypass
Water Lift	82"
Electrical Requirements	120 volts, 9 amp
Power Cord	25' long
Vacuum Hose	1.5" diameter, expandable to 12'
Solution Hose	12' long
Weight	30 pounds
Length x Width x Height	28" x 16" x 23"
Warranty*	90 days labor, 1 year machine, housing and accessories

\*See the actual warranty for full details.  
Specifications are subject to change without notice.